



SECTION A-A

Outsulation® RMD System™

Gable End With EPS Trim

NOTE:

1. FOR RAKE WITH OVERHANG REFER TO ORMD 0.0.32 AND 0.0.33.
2. FOR EPS THICKNESS (INCLUDING TRIM) EXCEEDING 64 MM (2 1/2"), BLOCKING SHOULD BE ADDED TO PROVIDE STRUCTURAL SUPPORT FOR THE ROOF SHEATHING.
3. FASTENERS ARE NOT REQUIRED WHEN BACKSTOP® NT IS USED AS THE WATER-RESISTIVE BARRIER.
4. DRYVIT GENESIS® OR GENESIS DM SHALL BE USED AS THE BASE COAT WHEN INSTALLING SYSTEMS WITH MECHANICAL FASTENERS.

The architecture, engineering and design of the project using the Dryvit products is the responsibility of the project's design professional. All systems must comply with local building codes and standards. This detail is for general information and guidance only and Dryvit specifically disclaims any liability for the use of this detail and for the architecture, design, engineering or workmanship of any project. The project design professional determines, in its sole discretion, whether this detail or a functionally equivalent alternative is best suited for the project. Use of a functionally equivalent detail does not violate Dryvit's warranty. This detail is subject to change without notice. Contact Dryvit to insure you have the most recent version.

| APPROVED BY: | REV: | DATE: |
|--------------|------|-------|
| RS | 7 | 02/08 |

