

# TABLE OF CONTENTS

DETAIL	PAGE
DRAINAGE MAT OPTION	ORMD 0.0.01
DUPONT™ TYVEK STUCCOWRAP® OPTION	ORMD 0.0.02
DRYVIT BACKSTOP® NT OPTION	ORMD 0.0.03
FASTENING PATTERN	ORMD 0.0.04
TERMINATION AT FOUNDATION	ORMD 0.0.05
GRADE LEVEL- TERMINATION AT CONCRETE CURB	ORMD 0.0.06
TERMINATION AT BRICK DETAIL	ORMD 0.0.07
OPENING PREP- SHEET TYPE WRB	ORMD 0.0.08
OPENING PREP- BACKSTOP NT WRB/ AQUAFLASH® SYSTEM OPTION	ORMD 0.0.09
OPENING PREP- BACKSTOP NT WRB/ BACKSTOP NT / GRID TAPE OPTION	ORMD 0.0.10
WINDOW ELEVATION	ORMD 0.0.11
ARCHED WINDOW HEAD	ORMD 0.0.12
WINDOW HEAD	ORMD 0.0.13
WINDOW HEAD J-TRACK OPTION FOR SELF FLASHING WINDOW	ORMD 0.0.14
WINDOW JAMB	ORMD 0.0.15
WINDOW SILL	ORMD 0.0.16
DOOR JAMB WITH INTEGRAL FLASHING	ORMD 0.0.17
DOOR JAMB WITH BRICK MOLD	ORMD 0.0.18
DOOR HEAD WITH INTEGRAL FLASHING	ORMD 0.0.19
DOOR HEAD WITH BRICK MOLD	ORMD 0.0.20
EPS PREPARATION AT WALL PENETRATIONS	ORMD 0.0.21
OUTSIDE CORNER- HIGH IMPACT	ORMD 0.0.22
INSIDE / OUTSIDE CORNERS	ORMD 0.0.23
EXPANSION JOINT AT FLOOR LINE	ORMD 0.0.24
CONCEALED FLOOR LINE EXPANSION JOINT	ORMD 0.0.25
WOOD FRAMED DECK- CROSS SECTION	ORMD 0.0.26
WOOD FRAMED DECK- CUT AWAY	ORMD 0.0.27

DETAIL	PAGE
SHUTTER AND DOWN SPOUT ATTACHMENT	OORMD 0.0.28
PENETRATIONS	OORMD 0.0.29
SEALANT CONFIGURATION OPTIONS	OORMD 0.0.30
AESTHETIC REVEALS	OORMD 0.0.31
SOFFIT TERMINATION	ORMD 0.0.32
SOFFIT WITH FRIEZE BOARD	ORMD 0.0.33
SOFFIT- INSULATED	ORMD 0.0.34
SOFFIT- UNINSUATED	ORMD 0.0.35
GABLE END WITH EPS TRIM	ORMD 0.0.36
GABLE END WITH WOOD TRIM	ORMD 0.0.37
PARAPET	ORMD 0.0.38
ROOF TO WALL FLASHING	ORMD 0.0.39
CHIMNEY ENCLOSURE	ORMD 0.0.40
SOFFIT VENT	ORMD 0.0.41

## NOTE

DRYVIT MAKES NO REPRESENTATION REGARDING CONFORMITY OF ITS SUGGESTIONS TO MODEL BUILDING CODES, ENGINEERING CRITERIA, SPECIFIC APPLICATIONS OR PROJECT LOCATIONS. ALL COMPONENTS INDICATED IN ILLUSTRATIONS, AS WELL AS OTHERS THAT MAY BE REQUIRED FOR THE INTEGRITY OF THE SYSTEM SHALL BE DESIGNED, DETAILED AND ENGINEERED BY REPRESENTATIVES OF THE ARCHITECT, OWNER OR CONTRACTOR TO BE IN CONFORMANCE WITH MODEL CODES, ARCHITECTURAL AND ENGINEERING REQUIREMENTS PERTAINING TO SPECIFIC BUILDING PROJECTS.

DRYVIT MAKES NO WARRANTY, EXPRESSED OR IMPLIED, AS TO THE ARCHITECTURAL DESIGN, ENGINEERING, OR WORKMANSHIP OF PROJECTS UTILIZING DRYVIT SYSTEMS OR PRODUCTS.

THE LIABILITIES OF DRYVIT SHALL BE AS STATED IN THE DRYVIT STANDARD WARRANTY. CONTACT DRYVIT FOR A FULL AND COMPLETE COPY OF THIS WARRANTY.

## Outsulation® RMD System™

The architecture, engineering and design of the project using the Dryvit products is the responsibility of the project's design professional. All systems must comply with local building codes and standards. This detail is for general information and guidance only and Dryvit specifically disclaims any liability for the use of this detail and for the architecture, design, engineering or workmanship of any project. The project design professional determines, in its sole discretion, whether this detail or a functionally equivalent alternative is best suited for the project. Use of a functionally equivalent detail does not violate Dryvit's warranty. This detail is subject to change without notice. Contact Dryvit to insure you have the most recent version.



APPROVED BY:	REV:	DATE:
RS	7	02/08